SAFETY DATA SHEET

Issuing Date 30-Jun-2017

Revision Date 28-Jun-2017

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier	
Product Name	XtraCare Lady's Dry Spray - Shower Fresh
Other means of identification	
Product Code(s)	1401805
Recommended use of the chemical	and restrictions on use
Recommended Use	Antiperspirants - Aerosol
Restrictions on use	No information available
Details of the supplier of the safety	data sheet
Supplier Identification	Ningbo Rejoice I/E Co., Ltd.
Address	Rm402, Unit 4, North Bank Fortune Centre,Jiangbei,Ningbo,315020,China Ningbo Zhejiang 315020 CN
Telephone	Phone:0086-574-87170403 Fax:0086-574-87170180
E-mail	powerwell2000@hotmail.com
Emergency telephone number	
Company Emergency Phone Number	0086-13586668388
	2. HAZARDS IDENTIFICATION

Classification

Flammable aerosols	Category 1
Gases under pressure	Liquefied Gas



Appearance White

Physical state Liquid spray Aerosol

Odor Fresh

GHS Label elements, including precautionary statements

Danger

Hazard statements

Extremely flammable aerosol Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Pressurized container: Do not pierce or burn, even after use Do not spray on an open flame or other ignition source

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 50 °C/122 °F

Other information

Toxic to aquatic life.

Unknown acute toxicity

88.2 % of the mixture consists of ingredient(s) of unknown toxicity 65.6 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

80.3 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

48.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

88.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

79.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Isobutane	75-28-5	23	-	-
Butane	106-97-8	15	-	-
Alcohol	64-17-5	8.8	-	-
Aluminum chlorohydrate	12042-91-0	7.5	-	-



Propane	74-98-6	2	-	-
Isopropyl myristate	110-27-0	1.6	-	-
BHT	128-37-0	0.1	-	-

4. FIRST AID MEASURES				
First aid measures				
General advice Inhalation	Show this safety data sheet to the doctor in attendance. Remove to fresh air.			
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.			
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.			
Ingestion	Clean mouth with water and drink afterwards plenty of water.			
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).			
Most important symptoms and effe	cts, both acute and delayed			
Symptoms	No information available.			
Indication of any immediate medica	al attention and special treatment needed			
Note to physicians	Treat symptomatically.			
	5. FIRE-FIGHTING MEASURES			
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.			
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.			
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.			
Hazardous Combustion Products	Carbon oxides.			
Explosion Data Sensitivity to Mechanical Impac Sensitivity to Static Discharge	et Yes. Yes.			
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.			

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures



Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.
Other Information	Ventilate the area.
Methods and material for containme	nt and cleaning up
Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

flames ignition cause i Handle area ec pressur mists. E	sonal protection equipment. Keep away from heat, hot surfaces, sparks, open and other ignition sources. No smoking. Do not spray on an open flame or other source. Take necessary action to avoid static electricity discharge (which might gnition of organic vapors). Use spark-proof tools and explosion-proof equipment. product only in closed system or provide appropriate exhaust ventilation. Keep in an uipped with sprinklers. Do not puncture or incinerate cans. Contents under e. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of ntainers.
---	--

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isobutane	STEL: 1000 ppm	N/A	N/A
75-28-5			
Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Alcohol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm



					TWA: 1000 ppm FWA: 1900 mg/m ³		TWA: 1900 mg/m ³
Aluminum chlorohydra 12042-91-0	te	TWA: 1 mg/m ³ particulate		(vacaleu)	- -		
Propane 74-98-6		TWA: 100) ppm		.: 1000 ppm 1800 mg/m³		IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
BHT 128-37-0		TWA: 2 mg/m ³ fraction and		(vacated)	TWA: 10 mg/m ³		TWA: 10 mg/m ³
Chemical name		Alberta	British C	Columbia	Ontario TWAE	V	Quebec
Isobutane 75-28-5			TWA: 10	000 ppm	TWA: 800 ppm T 1000 ppm STEL: 1000 pp		
Butane 106-97-8	Т	WA: 1000 ppm	1000	ppm TWA:) ppm 750 ppm	TWA: 800 ppm T 1000 ppm STEL: 1000 pp		TWA: 800 ppm TWA: 1900 mg/m ³
Alcohol 64-17-5		WA: 1000 ppm VA: 1880 mg/m ³	STEL: 1	000 ppm	STEL: 1000 pp	m	TWA: 1000 ppm TWA: 1880 mg/m³
Aluminum chlorohydrate 12042-91-0		-	TWA: 1.	.0 mg/m³	TWA: 1 mg/m	3	
Propane 74-98-6	Т	WA: 1000 ppm	TWA: 10	000 ppm	TWA: TWA: 1000	ppm	TWA: 1000 ppm TWA: 1800 mg/m³
BHT 128-37-0	Т	WA: 10 mg/m ³	TWA: 2	2 mg/m ³	TWA: 2 mg/m	3	STEL: 10 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering	controls	

Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

- **Eye/face protection** Tight sealing safety goggles.
- Hand protection Impervious gloves.

Skin and body protectionWear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties	
Physical state	Liquid spray; Aerosol
Appearance	White
Odor	Fresh
Color	No information available



Odor Threshold	Not applicable	
<u>Property</u>	Values	Remarks Method
рН	7	
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.8	
Water Solubility	Soluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/wate	erNot applicable	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Other Information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or



	fatal.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.
formation on toxicological effects	-
ymptoms	No information available.
umerical measures of toxicity	
cute Toxicity	
ATEmix (oral) ATEmix (dermal)	based on chapter 3.1 of the GHS document . 10,950.00 mg/kg 24,865.00 mg/kg 291.90 mg/L
65.6 % of the mixture consists of in 80.3 % of the mixture consists of in 48.2 % of the mixture consists of in 88.2 % of the mixture consists of in 79.4 % of the mixture consists of in	88.2 % of the mixture consists of ingredient(s) of unknown toxicity gredient(s) of unknown acute oral toxicity gredient(s) of unknown acute dermal toxicity gredient(s) of unknown acute inhalation toxicity (gas) gredient(s) of unknown acute inhalation toxicity (vapor) gredient(s) of unknown acute inhalation toxicity (dust/mist)
cute Toxicity he following values are calculated b ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-dust/mist) nknown acute toxicity 65.6 % of the mixture consists of in 80.3 % of the mixture consists of in 48.2 % of the mixture consists of in 88.2 % of the mixture consists of in	10,950.00 mg/kg 24,865.00 mg/kg 291.90 mg/L 88.2 % of the mixture consists of ingredient(s) of unknown toxicity gredient(s) of unknown acute oral toxicity gredient(s) of unknown acute dermal toxicity gredient(s) of unknown acute inhalation toxicity (gas) gredient(s) of unknown acute inhalation toxicity (vapor)

Component Information

Ob a mile al manue		Dama al L DEO	list statistic LOCO
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isobutane	-	-	= 658 mg/L (Rat)4 h
Butane	-	-	= 658 g/m ³ (Rat) 4 h
Alcohol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Aluminum chlorohydrate	= 9187 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
Propane	-	-	= 658 mg/L (Rat) 4 h
Isopropyl myristate	> 10000 mg/kg (Rat)	= 5 g/kg (Rabbit)	> 41 mg/L (Rat)1 h
BHT	= 890 mg/kg (Rat)	> 2000 mg/kg (Rat)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Classification based on data available for ingredients. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Alcohol 64-17-5	A3	Group 1	Known	Х
BHT 128-37-0	-	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen



IARC (International Agency for			
	Group 1 - Carcinogenic to Humans		
Group 3 - Not Classifiable as to C	Carcinogenicity in Humans		
NTP (National Toxicology Prog	ram)		
Known - Known Carcinogen			
OSHA (Occupational Safety and	d Health Administration of the US Department of Labor)		
X - Present			
Reproductive toxicity	No information available.		

STOT - single exposure	No information available.
STOT - repeated exposure	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aspiration hazard

Toxic to aquatic life.

No information available.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna (Water
			Microorganisms	Flea)
Alcohol	-	96h LC50: 12.0 - 16.0	EC50 = 34634 mg/L 30	48h LC50: 9268 - 14221
		mL/L (Oncorhynchus	min	mg/L 48h EC50: = 2 mg/L
		mykiss) 96h LC50: > 100	EC50 = 35470 mg/L 5	24h EC50: = 10800 mg/L
		mg/L (Pimephales	min	
		promelas) 96h LC50:		
		13400 - 15100 mg/L		
		(Pimephales promelas)		
Aluminum chlorohydrate	-	96h LC50: 100 - 500	-	-
		mg/L (Brachydanio rerio)		
Isopropyl myristate	72h EC50: > 100 mg/L	96h LC50: = 8400 mg/L	-	48h EC50: = 100 mg/L
	(Desmodesmus	(Brachydanio rerio)		
	subspicatus)			
BHT	72h EC50: = 6 mg/L	48h LC50: = 5 mg/L	EC50 = 7.82 mg/L 5 min	
	(Pseudokirchneriella	(Oryzias latipes)	EC50 = 8.57 mg/L 15 min	
	subcapitata) 72h EC50: >		EC50 = 8.98 mg/L 30 min	
	0.42 mg/L			
	(Desmodesmus			
	subspicatus)			

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Log Pow
Isobutane	2.88
Butane	2.89
Alcohol	-0.32
Propane	2.3
Isopropyl myristate	6
BHT	4.17

Mobility

No information available.

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
US EPA Waste Number	D001

California Hazardous Waste Codes 311

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Alcohol	Toxic
64-17-5	Ignitable

14. TRANSPORT INFORMATION

DOT Proper Shipping Name Hazard Class Description Emergency Response Guide Number	CONSUMER COMMODITY ORM-D CONSUMER COMMODITY, ORM-D 126
<u>TDG</u> UN-No. Proper Shipping Name Hazard Class Description	UN1950 AEROSOLS 2.1 UN1950, AEROSOLS, 2.1
<u>MEX</u> UN-No. Proper Shipping Name Hazard Class Description	UN1950 AEROSOLS 2.1 UN1950, AEROSOLS, 2.1
ICAO UN-No. Proper Shipping Name Hazard Class Description	UN1950 AEROSOLS 2.1 UN1950, AEROSOLS, 2.1
IATA UN-No. Proper Shipping Name Hazard Class ERG Code Description	UN1950 AEROSOLS, FLAMMABLE 2.1 10L UN1950, AEROSOLS, FLAMMABLE, 2.1
IMDG/IMO UN-No. Proper Shipping Name	UN1950 AEROSOLS



Hazard Class EmS-No. Description	2.1 F-D, S-U UN1950, AEROSOLS, 2.1
<u>RID</u> UN-No. Proper Shipping Name Hazard Class Classification code Description ADR/RID-Labels	UN1950 AEROSOLS 2.1 5F UN1950, AEROSOLS, 2.1 2.1
ADR UN-No. Proper Shipping Name Hazard Class Classification code Tunnel restriction code Description	UN1950 AEROSOLS 2.1 5F (D) UN1950, AEROSOLS, 2.1, (D)
ADN UN-No. Proper Shipping Name Hazard Class Classification code Special Provisions Description Hazard Labels Limited Quantity Ventilation	UN1950 AEROSOLS 2.1 5F 190, 327, 344, 625 UN1950, AEROSOLS, 2.1 2.1 1 L VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International InventoriesTSCAContact supplier for inventory compliance status.DSL/NDSLContact supplier for inventory compliance status.EINECS/ELINCSContact supplier for inventory compliance status.ENCSContact supplier for inventory compliance status.KECLContact supplier for inventory compliance status.PICCSContact supplier for inventory compliance status.AICSContact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances



AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Alcohol - 64-17-5	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusett s	Pennsylvania	Rhode Island	Illinois
Isobutane 75-28-5	Х	Х	Х		
Butane 106-97-8	Х	Х	Х		
Alcohol 64-17-5	Х	Х	Х		Х
Propane 74-98-6	Х	Х	Х		
BHT 128-37-0	Х	X	Х		

16. OTHER INFORMATION				
<u>NFPA</u>	Health hazards 1	Flammability 4	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 1	Flammability 4	Physical hazards 0	Personal Protection X
Prepared By	Product Stewardship			



	23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	30-Jun-2017
Revision Date	28-Jun-2017
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

