SAFETY DATA SHEET

Issuing Date No data available Revision Date 12-Sep-2014 Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name HD Oven Cleaner 13 OZ

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Oven Cleaner - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Ningbo Rejoice I/E Co., Ltd.

Supplier Address Rm402, Unit 4, North Bank Fortune Centre, Jiangbei, Ningbo, 315020, China

Ningbo Zhejiang 315020 CN

Supplier Phone Number Phone:0086-13586668388

Fax:0086-574-87170180

Contact Phone0086-13586668388 powerwell2000@hotmail.com

Supplier Email
Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements



Emergency Overview

Signal word

Danger

Hazard Statements

Causes skin irritation

Causes serious eye damage

Contains gas under pressure; may explode if heated



Appearance Clear

Physical State Liquid spray Aerosol

Odor Lemon

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

None

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.4% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.



Page 2/12

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Sodium hydroxide	1310-73-2	1 - 5	*
Butane	106-97-8	1 - 5	*
Propane	74-98-6	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Call 911 or emergency medical service. Remove and isolate contaminated

clothing and shoes. Show this safety data sheet to the doctor in attendance.

Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical

attention/advice.

Skin Contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific Hazards Arising from the Chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Uniform Fire Code Irritant: Gas

Aerosols: Level I

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Stop leak if you can do it without risk.

Other Information Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance

to evaporate.

Methods for cleaning upDo not direct water at spill or source of leak.

(U_L)

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Do not puncture or

incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact

with eyes.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Protect from sunlight.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sodium hydroxide	Sodium hydroxide Ceiling: 2 mg/m ³		IDLH: 10 mg/m ³
1310-73-2		(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
			TWA: 1800 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body ProtectionWear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or

smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES



Revision Date 12-Sep-2014

Physical and Chemical Properties

Physical State
Appearance
Liquid spray Aerosol
Clear
Odor
Lemon

Color No information available **Odor Threshold** No information available

None known

<u>Property</u> <u>Values</u> <u>Remarks/ Method</u>

Hq None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known No data available None known **Flash Point Evaporation Rate** No data available None known No data available Flammability (solid, gas) None known

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
Vapor pressure

No data available
No data available
No data available

Vapor density
No data available
Specific Gravity
No data available
Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/waterNo data available
Autoignition temperature
No data available
Decomposition temperature
No data available
No data available
No data available
No data available

Dynamic viscosity

Explosive properties

Oxidizing Properties

No data available
No data available
No data available

Other Information

Softening Point
VOC Content (%)

Particle Size

No data available
No data available
No data available

Particle Size Distribution



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Severely irritating to eyes. Causes serious eye damage. May cause

burns. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Irritating to skin. Prolonged contact may cause redness and

irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-
Butane 106-97-8	-	-	= 658 g/m³(Rat)4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h



Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. May cause

blindness. Burning.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Chronic Toxicity No known effect based on information supplied.

Target Organ Effects Respiratory system. Eyes. Skin. Central Nervous System (CNS).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 37,500.00 mg/kg (ATE) ATEmix (inhalation-gas)

6,631,546.70

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Sodium hydroxide	Toxic	
1310-73-2	Corrosive	

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY

Hazard Class ORM-D

Description CONSUMER COMMODITY, ORM-D

Emergency Response Guide 126

Number

<u>TDG</u>

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

MEX

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

ICAO

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

<u>IATA</u>

UN-No. UN1950

Proper Shipping Name AEROSOLS, NON-FLAMMABLE

Hazard Class 2.2

Description UN1950, AEROSOLS, NON-FLAMMABLE, 2.2

IMDG/IMO

UN-No. UN1950



Proper Shipping Name AEROSOLS Hazard Class 2.2 EmS No. F-D, S-U

Description UN1950, AEROSOLS, 2.2

RID

UN-No. UN1950
Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A

Description UN1950, AEROSOLS, 2.2

ADR

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A Tunnel restriction code (E)

Description UN1950, AEROSOLS, 2.2

<u>ADN</u>

UN-No. UN1950
Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A

Special Provisions 190, 327, 344, 625 **Description** UN1950, AEROSOLS, 2.2

Limited Quantity 1 L Ventilation VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

IECSC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard Yes
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

		Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances	
--	--	---------------	--------------------------------	------------------------	---------------------------	-------------------------------	--



Sodium hydroxide	1000 lb		X
1310-73-2			

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemic	al Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
	hydroxide 0-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

<u>California Proposition 65</u>
This product contains the following Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Sodium hydroxide 1310-73-2	Χ	Х	Χ	Х	
Butane 106-97-8	Х	Х	Х		
Propane 74-98-6	Χ	Х	Χ		
2-Butoxyethanol 111-76-2	Χ	Х	Χ	Х	Х

International Regulations

Mexico

National occupational exposure limits

reactional observational expectate infine				
	Component	Carcinogen Status	Exposure Limits	
	Sodium hydroxide 1310-73-2 (1 - 5)		Mexico: Ceiling 2 mg/m ³	
	Butane 106-97-8(1 - 5)		Mexico: TWA 800 ppm Mexico: TWA 1900 mg/m ³	

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

A - Compressed gases



	10. OTTIER INFORMATION						
NFPA	Health Hazards 3	Flammability 0	Instability 0	Physical and			
HMIS	Health Hazards 3	Flammability 0	Physical Hazard 0	Chemical Hazards - Personal Protection			

16 OTHER INFORMATION



Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 12-Sep-2014

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Page 12/12