SAFETY DATA SHEET

Issuing Date 18-Sep-2015 **Revision Date** 18-Sep-2015 **Revision Number** 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name **Alloy Wheel Cleaner**

Other means of identification

UN-No. UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use General Purpose Cleaner - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Ningbo Rejoice I/E Co., Ltd.

Supplier Address Rm402, Unit 4, North Bank Fortune Centre,Jiangbei,Ningbo,315020,China
Ningbo
Zhejiang
315020
CN

Supplier Phone Number Phone:0086-574-87170403
Fax:0086-574-87170180

Supplier Email powerwell2000@hotmail.com

Emergency telephone number

Company Emergency Phone Number 0086-13586668388

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 1 Sub-category C
Serious eye damage/eye irritation	Category 1

Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview

Signal word **Danger**

Hazard Statements
Causes severe skin burns and eye damage
Contains gas under pressure; may explode if heated

Appearance Clear **Physical state** Liquid spray Aerosol **Odor** Fresh

Precautionary Statements - Prevention
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response
Immediately call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Immediately call a POISON CENTER or doctor/physician

Ingestion
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage
Store locked up
Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity
1.5 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals
No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Sodium silicate	1344-09-8	1 - 5	*
Butane	106-97-8	1 - 5	*
Sodium hydroxide	1310-73-2	1 - 5	*
Propylene glycol monomethyl ether	107-98-2	1 - 5	*
Propane	74-98-6	1 - 5	*
Sodium nitrite	7632-00-0	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media
DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical
The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Uniform Fire Code Aerosols: Level II

Hazardous Combustion Products
Carbon oxides.

Explosion Data
Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cans.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Do not puncture or incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials. Protect from sunlight.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m^3	TWA: 800 ppm TWA: 1900 mg/m^3
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m^3	TWA: 2 mg/m^3 (vacated) Ceiling: 2 mg/m^3	IDLH: 10 mg/m^3 Ceiling: 2 mg/m^3
Propylene glycol monomethyl ether 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m^3 (vacated) STEL: 150 ppm	TWA: 100 ppm TWA: 360 mg/m^3 STEL: 150 ppm

		(vacated) STEL: 540 mg/m³	STEL: 540 mg/m³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection None required for consumer use. If there is a risk of contact:. Tight sealing safety goggles. Face protection shield.

Skin and body protection None required for consumer use. If there is a risk of contact:. Wear protective gloves and protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid spray, Aerosol		
Appearance	Clear	**Odor**	Fresh
Color	No information available	**Odor Threshold**	No information available

Property	**Values**	**Remarks Method**
pH	11	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	0.95	None known
Water Solubility	Soluble (> .?%)	None known
Solubility in other solvents	No data available	None known

Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability
Stable under recommended storage conditions.
Possibility of Hazardous Reactions
None under normal processing.
Hazardous Polymerization
Hazardous polymerization does not occur.

Conditions to avoid
Exposure to air or moisture over prolonged periods. Excessive heat.
Incompatible materials
Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products
Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on components). Prolonged skin contact causes burns. Symptoms may be delayed.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the

mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium silicate 1344-09-8	= 1153 mg/kg (Rat)	> 4640 mg/kg (Rabbit)	-
Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-
Propylene glycol monomethyl ether 107-98-2	= 5200 mg/kg (Rat)	= 13 g/kg (Rabbit)	= 54.6 mg/L (Rat) 4 h > 24 mg/L (Rat) 1 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Sodium nitrite 7632-00-0	= 85 mg/kg (Rat)	-	= 5.5 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sodium nitrite 7632-00-0		Group 2A		X

IARC (International Agency for Research on Cancer)
Group 2A - Probably Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
17,615.00 mg/kg
ATEmix (dermal)
81,533.00 mg/kg (ATE)
ATEmix (inhalation-gas)
6,631,546.70
ATEmix (inhalation-dust/mist)
3,640.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity
Harmful to aquatic life.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Sodium silicate 1344-09-8		96h LC50: 301 - 478 mg/L (Lepomis macrochirus) 96h LC50: = 3185 mg/L (Brachydanio rerio)		96h EC50: = 216 mg/L
Sodium hydroxide 1310-73-2		96h LC50: = 45.4 mg/L (Oncorhynchus mykiss)		
Propylene glycol monomethyl ether 107-98-2		96h LC50: = 20.8 g/L (Pimephales promelas) 96h LC50: 4600 - 10000 mg/L (Leuciscus idus)		48h EC50: = 23300 mg/L
Sodium nitrite 7632-00-0		96h LC50: 0.092 - 0.13 mg/L (Oncorhynchus mykiss) 96h LC50: 0.4 - 0.6 mg/L (Oncorhynchus mykiss) 96h LC50: 0.65 - 1 mg/L (Oncorhynchus mykiss) 96h LC50: = 2.3 mg/L (Pimephales promelas) 96h LC50: = 20 mg/L (Pimephales promelas) 96h LC50: = 0.19 mg/L (Oncorhynchus mykiss)		

Persistence and Degradability
No information available.

Bioaccumulation

Chemical Name	Log Pow
Butane 106-97-8	2.89
Propylene glycol monomethyl ether 107-98-2	-0.437
Propane 74-98-6	2.3
Sodium nitrite 7632-00-0	-3.7

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Sodium hydroxide 1310-73-2	Toxic Corrosive
Sodium nitrite 7632-00-0	Toxic Ignitable Reactive

14. TRANSPORT INFORMATION

DOT

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.2
Reportable Quantity (RQ) (RQ/% in mixture)	Sodium nitrite: RQ kg= 22700.00
Description	UN1950, Aerosols, 2.2, RQ
Emergency Response Guide Number	126

TDG

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Subsidiary class	8
Description	UN1950, Aerosols, 2.1 (8)

MEX

UN-No.	UN1950
Proper Shipping Name	Aerosols mixture
Hazard Class	2
Description	UN1950, Aerosols mixture, 2

ICAO Forbidden

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.2
Description	UN1950, Aerosols, 2.2

IATA

UN-No.	UN1950

Proper Shipping Name	Aerosols, non-flammable mixture
Hazard Class	2.2
Description	UN1950, Aerosols, non-flammable mixture, 2.2

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	Aerosols mixture
Hazard Class	2
EmS-No.	F-D, S-U
Description	UN1950, Aerosols mixture, 2

RID

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.2
Classification code	5A
Description	UN1950, Aerosols, 2.2

ADR

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.2 8
Classification code	5C
Tunnel restriction code	(E)
Description	UN1950, Aerosols, 2.2 8

ADN

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.2
Classification code	5C
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.2 (8)
Hazard Labels	2.2 + 8
Limited Quantity	1 L
Ventilation	VE04

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Sodium nitrite - 7632-00-0	7632-00-0	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No

Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000 lb			X
Sodium nitrite 7632-00-0	100 lb			X

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Sodium nitrite 7632-00-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65
This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Butane 106-97-8	X	X	X		
Propylene glycol monomethyl ether 107-98-2	X	X	X		
Sodium hydroxide 1310-73-2	X	X	X	X	
Propane 74-98-6	X	X	X		

International Regulations

Mexico
National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Butane 106-97-8 (1 - 5)		Mexico: TWA 800 ppm Mexico: TWA 1900 mg/m^3
Sodium hydroxide 1310-73-2 (1 - 5)		Mexico: Ceiling 2 mg/m^3

Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class
Not determined

16. OTHER INFORMATION

NFPA	**Health Hazards** 3	**Flammability** 0	**Instability** 0	**Physical and Chemical Hazards** -
HMIS	**Health Hazards** 3	**Flammability** 0	**Physical Hazard** 0	**Personal Protection** X

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	18-Sep-2015
Revision Date	18-Sep-2015
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet