# SAFETY DATA SHEET

Issuing Date 18-Sep-2015 Revision Date 18-Sep-2015 Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name Foaming Engine Degreaser

Other means of identification

**UN-No.** UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use General Purpose Cleaner - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Ningbo Rejoice I/E Co., Ltd.

Supplier Address Rm402, Unit 4, North Bank Fortune Centre, Jiangbei, Ningbo, 315020, China

Ningbo Zhejiang 315020 CN

**Supplier Phone Number** Phone:0086-574-87170403

Fax:0086-574-87170180

Supplier Email powerwell2000@hotmail.com

Emergency telephone number

**Company Emergency Phone** 

Number

0086-13586668388

# 2. HAZARDS IDENTIFICATION

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1



Gases under pressure Compressed gas

## GHS Label elements, including precautionary statements

**Emergency Overview** 

Signal word Danger

# Hazard Statements

Causes skin irritation

Causes serious eye damage

Contains gas under pressure; may explode if heated



**Appearance** Clear

Physical state Liquid spray Aerosol

Odor Fresh

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

## **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

#### Skin

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

## **Precautionary Statements - Storage**

Protect from sunlight. Store in a well-ventilated place

## **Precautionary Statements - Disposal**

None

## Hazards not otherwise classified (HNOC)

Not applicable

#### **Unknown Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity

#### Other information

No information available



Page 2/12

#### **Interactions with Other Chemicals**

No information available.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Butane	106-97-8	1 - 5	*
Tetrasodium pyrophosphate	7722-88-5	1 - 5	*
Sodium metasilicate	6834-92-0	1 - 5	*
Sodium hydroxide	1310-73-2	1 - 5	*
2-Butoxyethanol	111-76-2	1 - 5	*
Propane	74-98-6	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

# 4. FIRST AID MEASURES

## First aid measures

<u>General Advice</u> Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue

rinsing. Do not rub affected area. Seek immediate medical attention/advice.

**Skin contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

**Inhalation** Remove to fresh air. Get medical attention immediately if symptoms occur.

**Ingestion** Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Do NOT induce vomiting. Call a physician.

**Self-protection of the first aider** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

**Effects** 

Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

Page 3/12

# 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

## Specific hazards arising from the chemical

Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Uniform Fire Code Irritant: Liquid

Aerosols: Level III

#### **Hazardous Combustion Products**

Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge No.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Contents under pressure. Do not puncture or incinerate

cans.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Environmental precautions** 

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

## Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.



Page 4/12

\_\_\_\_\_

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Do not puncture or

incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact

with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Protect from sunlight.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Tetrasodium pyrophosphate 7722-88-5	-	(vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** None required for consumer use. If there is a risk of contact:. Tight sealing safety goggles.

**Skin and body protection**None required for consumer use. If there is a risk of contact:. Wear protective gloves and

protective clothing.

**Respiratory protection**No protective equipment is needed under normal use conditions. If exposure limits are



Page 5/12

exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** 

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **Physical and Chemical Properties**

Physical stateLiquid spray, AerosolAppearanceClearOdorFreshColorNo information availableOdor ThresholdNo information available

**Property** Values Remarks Method pН 11 None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known **Flash Point** No data available None known **Evaporation Rate** No data available None known No data available Flammability (solid, gas) None known Flammability Limit in Air **Upper flammability limit** No data available Lower flammability limit No data available Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** 0.95 None known Soluble (> .?%) Water Solubility None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known **Explosive properties** No data available

No data available

# **Other Information**

**Oxidizing properties** 

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

**Particle Size Distribution** 

**U** 

Page 6/12

\_\_\_\_\_

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

## **Chemical stability**

Stable under recommended storage conditions.

## **Possibility of Hazardous Reactions**

None under normal processing.

# **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

Excessive heat.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

## **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

**Eye contact** Specific test data for the substance or mixture is not available. (based on components).

Causes serious eye damage. Severely irritating to eyes. May cause irreversible damage to

eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based

on components). Prolonged contact may cause redness and irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

# **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Tetrasodium pyrophosphate 7722-88-5	> 2000 mg/kg (Rat)	-	-
Sodium metasilicate 6834-92-0	= 600 mg/kg (Rat)	-	-
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg ( Rabbit )	-
2-Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h

## Information on toxicological effects



Page 7/12

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. May cause

blindness. Burning.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3	Group 3		
111-76-2		•		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

Chronic Toxicity No known effect based on information supplied. Carcinogenic potential is unknown.

Target Organ Effects Respiratory system. Eyes. Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
11,506.00 mg/kg
ATEmix (dermal)
40,408.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
100.00 mg/l
ATEmix (inhalation-vapor)
733.00 ATEmix



# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Sodium metasilicate 6834-92-0		96h LC50: = 210 mg/L (Brachydanio rerio)		96h EC50: = 216 mg/L
Sodium hydroxide 1310-73-2		96h LC50: = 45.4 mg/L (Oncorhynchus mykiss)		
2-Butoxyethanol 111-76-2		96h LC50: = 1490 mg/L (Lepomis macrochirus) 96h LC50: = 2950 mg/L (Lepomis macrochirus)		48h EC50: > 1000 mg/L 24h EC50: 1698 - 1940 mg/L

# Persistence and Degradability

No information available.

#### **Bioaccumulation**

Chemical Name	Log Pow
Butane 106-97-8	2.89
2-Butoxyethanol 111-76-2	0.81
Propane 74-98-6	2.3

#### Other adverse effects

No information available.

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

**Disposal methods** 

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging** 

Dispose of contents/containers in accordance with local regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Sodium hydroxide	Toxic
1310-73-2	Corrosive

# 14. TRANSPORT INFORMATION

**DOT** 



\_\_\_\_\_

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2

**Description** UN1950, Aerosols, 2.2

Emergency Response Guide 126

Number

**TDG** 

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2

**Description** UN1950, Aerosols, 2.2

**MEX** 

UN-No. UN1950 Proper Shipping Name Aerosols

Hazard Class 2

**Description** UN1950, Aerosols, 2

<u>ICAO</u>

UN-No. UN1950 Proper Shipping Name Aerosols Hazard Class 2.2

**Description** UN1950, Aerosols, 2.2

IATA

**UN-No.** UN1950

Proper Shipping Name Aerosols, non-flammable

Hazard Class 2.2

**Description** UN1950, Aerosols, non-flammable, 2.2

IMDG/IMO

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2

**EmS-No.** F-D, S-U

**Description** UN1950, Aerosols, 2

**RID** 

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Classification code 5A

**Description** UN1950, Aerosols, 2.2

**ADR** 

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Classification code 5A
Tunnel restriction code (E)

**Description** UN1950, Aerosols, 2.2

ADN

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2

Classification code 5A

**Special Provisions** 190, 327, 344, 625 **Description** UN1950, Aerosols, 2.2



Hazard Labels 2.2 Limited Quantity 1 L Ventilation VE04

# 15. REGULATORY INFORMATION

## **International Inventories**

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard Yes
Reactive Hazard No

## **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide	1000 lb			X
1310-73-2				

## CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

## **US State Regulations**

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

## **U.S. State Right-to-Know Regulations**

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Butane 106-97-8	Х	Х	Х		
2-Butoxyethanol 111-76-2	Х	Х	Х	Х	Х
Sodium hydroxide	Х	Х	Х	Х	



1310-73-2				
Tetrasodium pyrophosphate 7722-88-5	X	X	Х	
Propane 74-98-6	X	Х	Х	

# International Regulations

#### Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Butane		Mexico: TWA 800 ppm
106-97-8 (1 - 5)		Mexico: TWA 1900 mg/m <sup>3</sup>
Sodium hydroxide		Mexico: Ceiling 2 mg/m <sup>3</sup>
1310-73-2 ( 1 - 5 )		
2-Butoxyethanol		Mexico: TWA 26 ppm
111-76-2 (1 - 5)		Mexico: TWA 120 mg/m <sup>3</sup>
		Mexico: STEL 75 ppm
		Mexico: STEL 360 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### **WHMIS Hazard Class**

Not determined

NFPA	Health Hazards 2	Flammability 0	Instability 0	Physical and Chemical Hazards
HMIS	Health Hazards 2	Flammability 0	Physical Hazard 0	Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

**Issuing Date** 18-Sep-2015 **Revision Date** 18-Sep-2015

Revision Note No information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

