SAFETY DATA SHEET

Issuing Date No data available Revision Date 15-Sep-2014 Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name 10oz Super Oxi Pet Stain Remover

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Bathroom and Tile Cleaner - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Ningbo Rejoice I/E Co., Ltd.

Supplier Address Rm402, Unit 4, North Bank Fortune Centre, Jiangbei, Ningbo, 315020, China

Ningbo Zhejiang 315020 CN

Supplier Phone Number Phone:0086-13586668388

Fax:0086-574-87170180

Contact Phone0086-13586668388 powerwell2000@hotmail.com

Supplier Email

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview



Signal word

Danger

Hazard Statements

Causes serious eye damage

Contains gas under pressure; may explode if heated



Appearance Clear Blue

Physical State Liquid spray Aerosol

Odor Citrus

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

None

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.501% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation

Harmful to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.



Page 2/12

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Butane	106-97-8	1 - 5	*
Sodium percarbonate	15630-89-4	1 - 5	*
Lauryl polyethylene glycol ether	9002-92-0	1 - 5	*
Diethylene glycol monobutyl ether	112-34-5	1 - 5	*
Propane	74-98-6	1 - 5	*
EDTA disodium salt, dihydrate	6381-92-6	1 - 5	*
Ammonium hydroxide	1336-21-6	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor

in attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek

immediate medical attention/advice.

Skin Contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Wash with soap and water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific Hazards Arising from the Chemical

Ruptured cylinders may rocket. Some may burn but none ignite readily.

Uniform Fire Code Aerosols: Level I

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Stop leak if you can do it without risk.

Other Information Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance

to evaporate.

Methods for cleaning upDo not direct water at spill or source of leak.



7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Do not puncture or

incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact

with eyes.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Protect from sunlight.

Incompatible Products Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Diethylene glycol monobutyl ether TWA: 10 ppm inhalable fraction and vapor		-	
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
			TWA: 1800 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or

smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES



Physical and Chemical Properties

Physical StateLiquid spray AerosolAppearanceClear BlueOdorCitrus

Color No information available Odor Threshold No information available

None known

Property Values Remarks/ Method

рH None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known No data available None known Flash Point None known **Evaporation Rate** No data available No data available Flammability (solid, gas) None known

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
Vapor pressure

No data available
No data available

Vapor density
No data available
Specific Gravity
No data available
Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/water No data available
Autoignition temperature
No data available
Decomposition temperature
No data available
No data available
Kinematic viscosity
No data available

Dynamic viscosity

Explosive properties

Oxidizing Properties

No data available

No data available

No data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available

No data available

No data available

Particle Size Distribution



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. Severely irritating to eyes.

Causes serious eye damage. May cause burns. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Sodium percarbonate 15630-89-4	= 1034 mg/kg (Rat)	-	-
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
Propane 74-98-6	-	-	= 658 mg/L (Rat)4 h
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-



Information on toxicological effects

Symptoms Erythema (skin redness). May cause blindness. Burning.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

Chronic Toxicity No known effect based on information supplied.

No information available.

Target Organ Effects Eyes. Central Nervous System (CNS).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
11,100.00 mg/kg
ATEmix (dermal)
60,612.00 mg/kg (ATE)
ATEmix (inhalation-gas)
5,968,392.00
ATEmix (inhalation-dust/mist)
150.00 mg/l

STOT - repeated exposure



12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Sodium percarbonate 15630-89-4	240h EC50: = 70 mg/L (Chlorella emersonii)	96h LC50: = 70.7 mg/L (Pimephales promelas)		48h EC50: = 4.9 mg/L
Diethylene glycol monobutyl ether 112-34-5	96h EC50: > 100 mg/L (Desmodesmus subspicatus)	96h LC50: = 1300 mg/L (Lepomis macrochirus)		24h EC50: = 2850 mg/L 48h EC50: > 100 mg/L
Ammonium hydroxide 1336-21-6		96h LC50: = 8.2 mg/L (Pimephales promelas)		48h EC50: = 0.66 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	Chemical Name California Hazardous Waste	
Sodium percarbonate 15630-89-4	Ignitable	
Ammonium hydroxide 1336-21-6	Toxic Corrosive	

14. TRANSPORT INFORMATION



DOT

Proper Shipping Name CONSUMER COMMODITY

Hazard Class ORM-D Emergency Response Guide 126

Number

TDG

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

MEX

UN-No. UN1950
Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

<u>ICAO</u>

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2

Description UN1950, AEROSOLS, 2.2

<u>IATA</u>

UN-No. UN1950

Proper Shipping Name AEROSOLS, NON-FLAMMABLE

Hazard Class 2.2

Description UN1950, AEROSOLS, NON-FLAMMABLE, 2.2

IMDG/IMO

 UN-No.
 UN1950

 Proper Shipping Name
 AEROSOLS

 Hazard Class
 2.2

 EmS No.
 F-D, S-U

Description UN1950, AEROSOLS, 2.2

<u>RID</u>

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A

Description UN1950, AEROSOLS, 2.2

ADR

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A Tunnel restriction code (E)

Description UN1950, AEROSOLS, 2.2

ADN

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.2 Classification code 5A

Special Provisions190, 327, 344, 625DescriptionUN1950, AEROSOLS, 2.2

Limited Quantity 1 L



Ventilation VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Diethylene glycol monobutyl ether - 112-34-5	112-34-5	1 - 5	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium hydroxide 1336-21-6	1000 lb			Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ammonium hydroxide	1000 lb		RQ 1000 lb final RQ
1336-21-6			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Butane 106-97-8	Х	Х	Х		
Diethylene glycol monobutyl ether 112-34-5			Х	Х	Х
Propane 74-98-6	Х	Х	Х		



2-Butoxyethanol 111-76-2	Х	Х	Х	Х	Х
Ammonium hydroxide 1336-21-6	X	Х	Х	X	

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Butane		Mexico: TWA 800 ppm
106-97-8 (1 - 5)		Mexico: TWA 1900 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

D2A - Very toxic materials A - Compressed gases



16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 1 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 3 Flammability 0 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 15-Sep-2014

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

